


### Product highlights ▾

- \* Linux operation system
- \* ARM cpu
- \* Digital signal and processor
- \* Continuous hard work for 10000 hours
- \* Energy saving design
- \* High penetration
- \* Good quality images



### Dimensional Drawing ▾



### Important Sizes :

Product Size: 2848\* 1095 \* 1535.5mm (L × W × H)

Tunnel Size: 810\* 655mm (width × height)



## Product Details

### General Specifications

Unit weight	650kgs
Unit size	2848(L)*1095(W)*1535.5(H) mm
Tunnel size(mm)	810(L)*655(W)
Conveyor Speed(m/s)	0.2
Conveyor height(mm)	341
Conveyor Max Load(kgs)	200
Penetration	Typical 27mm steel, guarantee 27mm steel
Wire Resolution	Typical AWG34, guarantee AWG32
X-Ray dosage each inspection	Typical 1.1 $\mu$ Gy/h, guarantee 1.5 $\mu$ Gy/h
Boundary Leakage	Typical 0.8 $\mu$ Gy/h, guarantee 1.0 $\mu$ Gy/h
Power consumption	Max.1.0KVA
S/N ratio	<60dB
Film Safety	Guarantee ASA/ISO1600 Film

### Configuration

X-Ray generator	140KV, oil cooling, from top to bottom
Computer	CPU: CPU: Cortex A9
Monitor	Dell or Acer, 17" LED screen, resolution 1280*1024 pixels
Operation table	Double screen console
Keyboard	Made by Safeway
Operation System	LINUX

### Software

Image Enhancement	Color/BW, negative,high/lowpenetration, organic /inorganic Stripping, general enhancement, and pseudo color,etc.
Image Recall	30 images recallable,retrieval.
Image Archive	Up to 500,000 images stored automatically, enable transferring to USB disk, and converting to JPG, BMP and other general formats.
Other Functions	Fault diagnosis, system time setting, detection blind dots delete, x-ray source setting(analoge or digital), alarm setting, images setting, software register, user management, TIP report, data setting(machine working time, x-ray source working time, baggage counter, etc.)
Network Applications	Multiple remote applications available based on Ethernet LAN and windows platform, such as image centralized storage and identify, recheck workstation, and network TIP, etc ( Optional).

### Operating Environment

Operation temperature/Humidity	5C-40C / 0%-90%(non-condensing)
Storage temperature/Humidity	-40C-70C / 5%-95%(non-condensing)
Operation Power	220VAC( $\pm$ 10%) 50 $\pm$ 3Hz (Optional: 100VAC,110VAC,120VAC,200VAC)

## SAFEGWAY INSPECTION SYSTEM LIMITED

First Factory: BuildingA, QiFeng Digital Park, BaiNiKeng, PingHu Street, LongGang, Shenzhen, China

Second Factory: Building B, ShengLongXing Industrial Park, LongTeng Road, PingDi Street, LongGang, Shenzhen, China

Tel: +86 - 755-6195 5772 / Fax: +86 - 755-6195 5788

Mobile&Whatsapp: + 86- 136 7021 3490 Skype: sophia.xiong8105

Email: sophia@cargovehicleinspection.com

Website: www.cargovehicleinspection.com

